

Halo ProEx

The Intrinsically Safe Lone Worker Alarm



HALO Pro Ex is an intrinsically safe 3G/GSM/GNSS personal alarm device designed to protect lone workers in explosive hazardous areas.



Dedicated alarm device

- ManDown++, Amber alert
- SOS key for panic situations
- 2-way voice
- IP67 waterproof



Small and smart

- Plain text On-Screen Messages
- LCD display with guiding symbols
- Pre-programmable status keys



ATEX/IECEX approved

- II 2 G Ex ib IIC T4 Gb
- II 2 D Ex ib IIIC T130°C Db
- VTT 16 ATEX 040X / IECEX VTT 16.0009X



Location fusion

- Using all means to find the person in distress
- HALO Point Netloc and HALO Point AGPS
- HALO Beacon SRD on-site locating devices



HALO life cycle economies

- Support services
- Engineered and manufactured in-house by HALO



Remote device management

- HALO Point Remote Configurator
- Saves time and money in customer support

Dedicated lone worker alarm

Duty of care requires employers to give lone workers means to alert help. Depending on risk assessment, a dedicated alarm device may be required.

- Automatic ManDown++ function can trigger alert if user is incapacitated.
- When entering a risky situation, enhanced monitoring can be requested with Amber alert. It can trigger alert in ARC also in absence of GSM connection.****

ATEX/IECEX compliance

HALO Pro Ex complies with ATEX standards 60079-0:2012/60079-11:2012 and IECEX standards 60079-0:2011/60079-11:2011.



Efficient deployment

Remote configuration makes HALO devices fast to deploy and flexible to operate.

Alarm monitoring and tracking

All HALO Lone Worker systems are provided with 24/7/365 monitoring from our dedicated Alarm Receiving Centre (ARC).

Time & Attendance monitoring

Optionally, HALO personal alarms can register attendance by swiping HALO Tag RF identifiers.



HALO Pro Ex

Technical specification

Compatibility and communication

- Communicates with all systems using MPTP (Mobile Phone Telematics Protocol) both SMS and GPRS.
- Tracking and alert messages include information on GPS (Outdoor) / HALO Beacon (Indoors).

Provisioning and security

- Remote or local configuration
- Authorisation of remote and local access

Mechanics

- Dimensions: 20 mm x 45 mm x 94 mm
- Weight: 114 g including battery
- Waterproof (IP67) and shock resistant

Key telematics functionality

- Manual alert through SOS key
- ManDown++ alarm with optional alert triggers: device orientation and non-movement, free fall and impact
- Amber alert (timer alert, local + server based)
- Two-way 3G/GSM voice with speaker
- Device and user status messages
- Interactive on-screen messages
- GPS / HALO Beacon SRD tracking*
- Geofence

ATEX/IECEX approved

- II 2 G Ex ib IIC T4 Gb
- II 2 D Ex ib IIIC T130° C Db
- VTT 16 ATEX 040X / IECEx VTT 16.0009X

Key technical features

- Quad-band GSM (850/900/1800/1900 MHz)
- 5-band 3G (800/850/900/1900/2100 MHz)
- Built-in GSM, SRD and GPS antennas
- Operating temperature -20° C.. +40° C
- Alert tones
- Vibrating alert

Operating time

- Rechargeable 1300 mAh Li-ion battery
- Typical operating times, GPS/GPRS reporting**
 - 7 days (1 GPS report / hr)
 - 4 days (1 GPS report / 10 min)
 - 24 hours (1 GPS report / min)
 - 8 hours (1 GPS report / 5 sec)
 - Up to 12 days (GSM standby only)
- Recharging time*** < 4 hrs for 95 %
- NOTE! Charging allowed only with HALO Ex charger of device type CME92EU (or with USB cable FME92EU).

GNSS

- High performance 48-channel receiver
- Multi constellation GNSS receiver (GPS, Glonass, Galileo and BeiDou)
- Time to first fix: Hot start 1 s; cold start < 35 s
- Extended ephemeris on-board generation
- Motion based GPS control
- AGPS via HALO Point Services

Display and keys

- Dedicated ergonomic SOS key
- Backlit LCD display with guiding symbols
- Pre-programmable quick dial / status keys
- Answer
- Power On / Off / End call

Sales package content

- HALO Pro Ex personal alarm device with integral battery
- HALO Ex USB cable and HALO Ex charger with adapter of choice (EU/UK/AU)
- User and safety documents

Optional device features

- SRD (short range device) compatibility*

Accessories


- HALO ATEX SRD devices:
 - HALO Beacon Ex SRD locating device*
- Non-ATEX SRD devices:
 - HALO Beacon SRD locating device*
 - HALO Tag SRD RF identifier*
 - HALO Button SRD wireless alarm*

Software and resources

- HALO Configurator PC app
- HALO FirmwareLoader PC app
- HALO WebFinder monitoring SaaS
- HALO Integrator Kit for ARC integration

HALO Point Services

- Remote Configurator: turn-key service to manage all device settings over the air
- Netloc: turn-key cellular location service
- AGPS: turn-key service to speed up GPS



Halo Security Ltd
 Tel: +353 21 485 8986
info@halosecurity.ie
www.halosecurity.ie